

## Refrigerated counter S4-150 MA



- ▶ Constant, even refrigeration temperature inside
  - ✓ Cooling: Circulating air
  - ✓ Temperature control in 0.1°C steps
- ▶ Four drawers
  - ✓ Refrigerated
  - ✓ Gastronorm: 1/1 GN
  - ✓ Max. depth of GN containers: 3 x 150 mm, 1 x 100 mm
- ▶ With upturned edge
  - ✓ 50 mm

### Description

One appliance, two uses: The convection cooling ensures a constant, even refrigeration temperature inside this four-drawer refrigerated counter. Thanks to its high-quality and robust stainless steel surface, the appliance can be integrated perfectly into any kitchen and can also be used as a work surface.

### Features

• Material:	Chrome-nickel steel
• Power load:	0,35 kW   230 V   50 Hz
• Important information:	-
• Height-adjustable feet:	Yes
• Temperature range:	0 °C to 10 °C
• Temperature control:	Electronic In 0.1 °C steps
• Control unit:	Electronic Knob
• Control lamp:	ON/OFF
• Height adjustable:	850 mm to 900 mm
• Tilting:	50 mm
• GWP:	3
• Climate class:	4
• Energy efficiency class:	C (EU No. 2015 / 1094)
• Energy consumption:	956 kWh / an
• Cooling:	Circulating air

▶ Continue on the next page

## Refrigerated counter S4-150 MA

- Coolant: R600a / 0,064 kg
- Digital display: Yes
- Depth GN container max.: 3 x 150 mm, 1 x 100 mm
- Drip water evaporation: Yes
- ON/OFF switch: Yes
- Thermostat: Yes
- Material work surface: Stainless steel
- Including: -
- Available on request: Refrigerated counter with swivel castors
- Number of drawers: 4
- Width drawer: 299 mm
- Depth drawer: 572 mm
- Height drawer: 190 mm
- Drawers refrigerated: Yes
- Norm-format drawers: 1/1 GN
- Size: W 1,342 x D 700 x H 850 mm
- Weight: 112 kg



## Refrigerated counter S4-150 MA

### Add on Products

#### Oil and grease remover F1L



- Content: 6 x 1 litre
- Model: Liquid
- HACCP compliant: Yes
- Chlorine-free: Yes
- Phosphate-free: Yes
- Including: -
- Order quantity unit: 1 box (6 bottles)

Code-No. 173276  
GTIN 4015613773339

#### Stainl.steel polish.spray 500ml can



- Content / can: 500 ml
- Application: Remove heavy soiling such as grease residue first  
Do not spray onto hot surfaces
- allow them to cool down first:

Code-No. 173031  
GTIN 4015613360195