

COOL PRODUCTS WORLDWIDE



FSC1000S BLACK

Glass Door Merchandiser

Product Features

- Illuminated canopy
- Internal vertical light
- · Adjustable shelves
- Adjustable feet
- Ventilated cooling
- LED interior light with switch
- Self-closing sliding glass doors
- Adjustable feet with rollers to rear

Black 2-door display cooler with canopy

The TEFCOLD FSC-S Black range is available in two sizes - 1m and 1.2 metres wide. The black exterior is popular for contemporary shop fit-outs helping to give a more modern look. The black interior combined with vertical LED lighting really help the product stand out and catch the eye. The unit is suitable for drinks, dairy (milk, cheese, etc) as well as pre-packed sandwiches. The fridge is ideal for convenience stores, delis, sandwich shops and cafes.

Measures and Content		
Temperature Range	°C	+2 to +10
Climate Class		4
Gross / Net Weight	kg	164 / 159
Gross / Net Volume	I	771 / 524
Design and Material		
Door Number & Type	2 self-c	losing sliding glass doors
Tempered glass		Yes
Door Reversible		No
Shelves Number & Type		5 wire shelves black
Shelf Color		Black
Shelf Dimensions		870 x 470 mm
Bottom Shelf Dimensions		870 x 475
Max load on Shelves	kg/m²	196
Canopy Type		L-Shape
Canopy Light		LED
Feet / Legs		4 adjustable feet
Castors		4 rollers
Exterior Finish		Black
Interior Finish		Black (RAL9005)
Interior Light		LED
Lock		Yes
Cooling and Functions		
Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic
Refrigerant		
Refrigerant Charge		R290
The trigger date of the top of	g	R290 120
Thermometer	g	
	g	120
Thermometer	g	120
Thermometer Power and Consumption	g	120 Yes
Thermometer Power and Consumption Energy Class	g kWh/24h	120 Yes
Thermometer Power and Consumption Energy Class Max Ambient		120 Yes F 30°C at 55% RH
Thermometer Power and Consumption Energy Class Max Ambient Energy Consumption	kWh/24h	120 Yes F 30°C at 55% RH 5.96
Thermometer Power and Consumption Energy Class Max Ambient Energy Consumption Annual Energy Consumption	kWh/24h	F 30°C at 55% RH 5.96 2175
Thermometer Power and Consumption Energy Class Max Ambient Energy Consumption Annual Energy Consumption Power	kWh/24h kWh/year	120 Yes F 30°C at 55% RH 5.96 2175 13 Amp
Thermometer Power and Consumption Energy Class Max Ambient Energy Consumption Annual Energy Consumption Power Input Power	kWh/24h kWh/year	120 Yes F 30°C at 55% RH 5.96 2175 13 Amp 450
Thermometer Power and Consumption Energy Class Max Ambient Energy Consumption Annual Energy Consumption Power Input Power Voltage / Frequency	kWh/24h kWh/year W V/Hz	120 Yes F 30°C at 55% RH 5.96 2175 13 Amp 450 220-240/50
Thermometer Power and Consumption Energy Class Max Ambient Energy Consumption Annual Energy Consumption Power Input Power Voltage / Frequency Noise Level	kWh/24h kWh/year W V/Hz	120 Yes F 30°C at 55% RH 5.96 2175 13 Amp 450 220-240/50
Thermometer Power and Consumption Energy Class Max Ambient Energy Consumption Annual Energy Consumption Power Input Power Voltage / Frequency Noise Level Dimensions	kWh/24h kWh/year W V/Hz dB(A)	120 Yes F 30°C at 55% RH 5.96 2175 13 Amp 450 220-240/50 48
Thermometer Power and Consumption Energy Class Max Ambient Energy Consumption Annual Energy Consumption Power Input Power Voltage / Frequency Noise Level Dimensions Internal Dimension (WxDxH)	kWh/24h kWh/year W V/Hz dB(A)	120 Yes F 30°C at 55% RH 5.96 2175 13 Amp 450 220-240/50 48





Illuminated canopy

Sliding doors