



FSC1200H BLACK


Glass Door Merchandiser

Product Features

- Illuminated canopy
- · Internal vertical light
- Black interior and exterior
- Adjustable shelves
- Ventilated cooling
- · Hinged alu-framed glass door
- Adjustable feet with rollers to rear
- · Self-closing doors

The FSC-H Black range combines a quality unit at a very competitive price. Excellent build quality with a powerful fan assisted refrigeration system, sturdy hinged door, and LED light canopy that can have branding added to create extra impact. The black interior combined with the excellent vertical LED lighting (2 light strips on each door) really helps product stand out to customers.

Measures and Content		
Temperature Range	°C	+2 to +10
Climate Class		4
Gross / Net Weight	kg	189 / 174
Gross / Net Volume	I	1082 / 645
Design and Material		
Door Number & Type		2 hinged glass doors
Tempered glass		Yes
Door Reversible		No
Shelves Number & Type		5 wire shelves black
Shelf Color		Black
Shelf Dimensions		1072 x 540 mm
Bottom Shelf Dimensions		1070 x 475
Max load on Shelves	kg/m²	196
Canopy Type		L-Shape
Canopy Light		LED
Feet / Legs		4 adjustable feet
Castors		4 rollers
Exterior Finish		Black RAL9005
Interior Finish		Black (RAL9005)
Interior Light		LED
Lock		Yes
Cooling and Functions		
Type of Controller		Electronic
		Ventilated
Type of Cooling		Veritilated
Type of Cooling Type of Defrost		Automatic
Type of Defrost	g	Automatic
Type of Defrost Refrigerant	g	Automatic R290
Type of Defrost Refrigerant Refrigerant Charge	g	Automatic R290 120
Type of Defrost Refrigerant Refrigerant Charge Thermometer Power and Consumption Energy Class	g	Automatic R290 120
Type of Defrost Refrigerant Refrigerant Charge Thermometer Power and Consumption	g	Automatic R290 120 Yes
Type of Defrost Refrigerant Refrigerant Charge Thermometer Power and Consumption Energy Class	g kWh/24h	Automatic R290 120 Yes
Type of Defrost Refrigerant Refrigerant Charge Thermometer Power and Consumption Energy Class Max Ambient		Automatic R290 120 Yes F 30°C at 55% RH
Type of Defrost Refrigerant Refrigerant Charge Thermometer Power and Consumption Energy Class Max Ambient Energy Consumption	kWh/24h	Automatic R290 120 Yes F 30°C at 55% RH 6.8
Type of Defrost Refrigerant Refrigerant Charge Thermometer Power and Consumption Energy Class Max Ambient Energy Consumption Annual Energy Consumption	kWh/24h	Automatic R290 120 Yes F 30°C at 55% RH 6.8 2482
Type of Defrost Refrigerant Refrigerant Charge Thermometer Power and Consumption Energy Class Max Ambient Energy Consumption Annual Energy Consumption Power	kWh/24h kWh/year	Automatic R290 120 Yes F 30°C at 55% RH 6.8 2482 13 Amp
Type of Defrost Refrigerant Refrigerant Charge Thermometer Power and Consumption Energy Class Max Ambient Energy Consumption Annual Energy Consumption Power Input Power	kWh/24h kWh/year	Automatic R290 120 Yes F 30°C at 55% RH 6.8 2482 13 Amp 880
Type of Defrost Refrigerant Refrigerant Charge Thermometer Power and Consumption Energy Class Max Ambient Energy Consumption Annual Energy Consumption Power Input Power Voltage / Frequency	kWh/24h kWh/year W V/Hz	Automatic R290 120 Yes F 30°C at 55% RH 6.8 2482 13 Amp 880 220-240/50
Type of Defrost Refrigerant Refrigerant Charge Thermometer Power and Consumption Energy Class Max Ambient Energy Consumption Annual Energy Consumption Power Input Power Voltage / Frequency Noise Level	kWh/24h kWh/year W V/Hz	Automatic R290 120 Yes F 30°C at 55% RH 6.8 2482 13 Amp 880 220-240/50
Type of Defrost Refrigerant Refrigerant Charge Thermometer Power and Consumption Energy Class Max Ambient Energy Consumption Annual Energy Consumption Power Input Power Voltage / Frequency Noise Level Dimensions	kWh/24h kWh/year W V/Hz dB(A)	Automatic R290 120 Yes F 30°C at 55% RH 6.8 2482 13 Amp 880 220-240/50 48
Type of Defrost Refrigerant Refrigerant Charge Thermometer Power and Consumption Energy Class Max Ambient Energy Consumption Annual Energy Consumption Power Input Power Voltage / Frequency Noise Level Dimensions Internal Dimension (WxDxH)	kWh/24h kWh/year W V/Hz dB(A)	Automatic R290 120 Yes F 30°C at 55% RH 6.8 2482 13 Amp 880 220-240/50 48



Illuminated canopy

LED light