



MILLENNIUM ST20

Ventilated Scoop Ice Cream Display

Product Features

- Great product visibility
- Flat glass top
- Accepts Napoli pans (not supplied)
- LED interior light with switch
- Digital controller and temperature display
- Front glass hinges forward if required
- Double glazed glass on sides
- Heated glass to help prevent condensation
- Glass rear sliding doors

Professional 20 scoop ventilated ice cream display with

The Millennium ST20 ice cream display cabinet is the epitome of luxury for discerning ice cream retailers. This 20 napoli pan display is designed to showcase your ice cream in the most impressive way possible. Contemporary flat glass that is heated to reduce minimise condensation, the display creates a stunning visual appeal, while the efficient, ventilated cooling system keeps your ice cream or gelato at the perfect serving temperature, ensuring that it remains fresh and delicious. Features rear sliding doors and the front glass hinges up to make cleaning easier. If you're looking for a high-end scooping display cabinet that truly sets you apart, the Millennium ST20 is the ideal choice.

Serving Capacity Storage capacity (under) Total Display Area Total Display Area Total Display Area Total Display Area Tomeperature Range C Gross / Net Weight Registrate Interior Finish Refrigerant Charge Refrigerant Charge Refrigerant Charge Refrigerant Charge Refrigerand Consumption Energy Class Max Ambient Energy Consumption Ene	Measures and Content		
Total Display Area m² 1.19 Temperature Range °C -20 to -14 Climate Class 7 Gross / Net Weight kg 421 / 363 Gross / Net Volume I 1080 / 201 Design and Material Exterior Finish White Interior Light LED Cooling and Functions Type of Cooling Ventilated Type of Defrost Automatic, hot gas Refrigerant R290 Refrigerant Charge g 2 x 148 Thermometer Yes Power and Consumption Energy Class D Max Ambient 35°C at 75% RH Energy Consumption kWh/24h 29.75 Annual Energy Consumption kWh/year 10859 Power 16 Amp Single Phase Commando Socket Input Power W 2560 Voltage / Frequency V/Hz 220-240/50 Noise Level dB(A) 58 Dimensions Internal Dimension (WxDxH) mm 1826 x 1054 x 1356 Packed Dimension (WxDxH) mm 1826 x 1054 x 1356 Packed Dimension (WxDxH) mm 1826 x 1054 x 1356	Serving Capacity		20 Napoli Pans (5 L)
Temperature Range °C -20 to -14 Climate Class 7 Gross / Net Weight kg 421 / 363 Gross / Net Volume I 1080 / 201 Design and Material Exterior Finish White Interior Light LED Cooling and Functions Type of Cooling Ventilated Type of Defrost Automatic, hot gas Refrigerant Charge g 2 x 148 Thermometer Yes Power and Consumption Energy Class D Max Ambient 35°C at 75% RH Energy Consumption kWh/24h 29.75 Annual Energy Consumption kWh/year 10859 Power 16 Amp Single Phase Commando Socket Input Power W 2560 Voltage / Frequency V/Hz 220-240/50 Noise Level dB(A) 58 Dimensions Internal Dimension (WxDxH) mm External Dimension (WxDxH) mm 1826 x 1054 x 1356	Storage capacity (under)		No Under Storage
Climate Class 7 Gross / Net Weight kg 421 / 363 Gross / Net Volume I 1080 / 201 Design and Material Exterior Finish White Interior Light LED Cooling and Functions Type of Cooling Ventilated Type of Defrost Automatic, hot gas Refrigerant R290 Refrigerant Charge g 2 x 148 Thermometer Yes Power and Consumption Energy Class D Max Ambient 35°C at 75% RH Energy Consumption kWh/24h 29.75 Annual Energy Consumption kWh/year 10859 Power 16 Amp Single Phase Commando Socket Input Power W 2560 Voltage / Frequency V/Hz 220-240/50 Noise Level dB(A) 58 Dimensions Internal Dimension (WxDxH) mm External Dimension (WxDxH) mm External Dimension (WxDxH) mm External Dimension (WxDxH) mm External Dimension (WxDxH) mm 1826 x 1054 x 1356	Total Display Area	m²	1.19
Gross / Net Weight kg 421 / 363 Gross / Net Volume I 1080 / 201 Design and Material Exterior Finish White Interior Light LED Cooling and Functions Type of Cooling Ventilated Type of Defrost Automatic, hot gas Refrigerant Charge g 2 x 148 Thermometer Yes Power and Consumption Energy Class D Max Ambient 35°C at 75% RH Energy Consumption kWh/24h 29.75 Annual Energy Consumption kWh/year 10859 Power 16 Amp Single Phase Commando Socket Input Power W 2560 Voltage / Frequency V/Hz 220-240/50 Noise Level dB(A) 58 Dimensions Internal Dimension (WxDxH) mm 1826 x 1054 x 1356 Packed Dimension (WxDxH) mm 1826 x 1054 x 1356 Packed Dimension (WxDxH) mm 2000 x 1150 x 1620	Temperature Range	°C	-20 to -14
Gross / Net Volume Design and Material Exterior Finish White Interior Light LED Cooling and Functions Type of Cooling Ventilated Type of Defrost Automatic, hot gas Refrigerant Re290 Refrigerant Charge g 2 x 148 Thermometer Yes Power and Consumption Energy Class D Max Ambient 35°C at 75% RH Energy Consumption kWh/24h 29.75 Annual Energy Consumption kWh/year 10859 Power 16 Amp Single Phase Commando Socket Input Power W 2560 Voltage / Frequency V/Hz 220-240/50 Noise Level dB(A) 58 Dimensions Internal Dimension (WxDxH) mm External Dimension (WxDxH) mm External Dimension (WxDxH) mm External Dimension (WxDxH) mm 1826 x 1054 x 1356 Packed Dimension (WxDxH) mm 2000 x 1150 x 1620	Climate Class		7
Design and Material Exterior Finish White Interior Light LED Cooling and Functions Type of Cooling Ventilated Type of Defrost Automatic, hot gas Refrigerant R290 Refrigerant Charge g 2 x 148 Thermometer Yes Power and Consumption Energy Class D Max Ambient 35°C at 75% RH Energy Consumption kWh/24h 29.75 Annual Energy Consumption kWh/year 10859 Power 16 Amp Single Phase Commando Socket Input Power W 2560 Voltage / Frequency V/Hz 220-240/50 Noise Level dB(A) 58 Dimensions Internal Dimension (WxDxH) mm External Dimension (WxDxH) mm External Dimension (WxDxH) mm External Dimension (WxDxH) mm External Dimension (WxDxH) mm 1826 x 1054 x 1356 Packed Dimension (WxDxH) mm 2000 x 1150 x 1620	Gross / Net Weight	kg	421 / 363
Exterior Finish White Interior Finish Stainless steel Interior Light LED Cooling and Functions Type of Cooling Ventilated Type of Defrost Automatic, hot gas Refrigerant R290 Refrigerant Charge g 2 x 148 Thermometer Yes Power and Consumption Energy Class D Max Ambient 35°C at 75% RH Energy Consumption kWh/24h 29.75 Annual Energy Consumption kWh/year 10859 Power 16 Amp Single Phase Commando Socket Input Power W 2560 Voltage / Frequency V/Hz 220-240/50 Noise Level dB(A) 58 Dimensions Internal Dimension (WxDxH) mm External Dimension (WxDxH) mm 2000 x 1150 x 1620	Gross / Net Volume	1	1080 / 201
Interior Finish Stainless steel Interior Light LED Cooling and Functions Type of Cooling Ventilated Type of Defrost Automatic, hot gas Refrigerant R290 Refrigerant Charge g 2 x 148 Thermometer Yes Power and Consumption Energy Class D Max Ambient 35°C at 75% RH Energy Consumption kWh/24h 29.75 Annual Energy Consumption kWh/year 10859 Power 16 Amp Single Phase Commando Socket Input Power W 2560 Voltage / Frequency V/Hz 220-240/50 Noise Level dB(A) 58 Dimensions Internal Dimension (WxDxH) mm External Dimension (WxDxH) mm External Dimension (WxDxH) mm 1826 x 1054 x 1356 Packed Dimension (WxDxH) mm 1826 x 1054 x 1356	Design and Material		
Interior Light LED Cooling and Functions Type of Cooling Ventilated Type of Defrost Automatic, hot gas Refrigerant R290 Refrigerant Charge g 2 x 148 Thermometer Yes Power and Consumption Energy Class D Max Ambient 35°C at 75% RH Energy Consumption kWh/24h 29.75 Annual Energy Consumption kWh/year 10859 Power 16 Amp Single Phase Commando Socket Input Power W 2560 Voltage / Frequency V/Hz 220-240/50 Noise Level dB(A) 58 Dimensions Internal Dimension (WxDxH) mm External Dimension (WxDxH) mm External Dimension (WxDxH) mm 1826 x 1054 x 1356 Packed Dimension (WxDxH) mm 2000 x 1150 x 1620	Exterior Finish		White
Cooling and Functions Type of Cooling Type of Defrost Refrigerant Refrigerant Refrigerant Charge Refrigerant Charge Power and Consumption Energy Class Max Ambient Energy Consumption Energy Consumption kWh/24h Energy Consumption kWh/year 10859 Power 16 Amp Single Phase Commando Socket Input Power V/Hz 220-240/50 Voltage / Frequency V/Hz Dimensions Internal Dimension (WxDxH) mm 1826 x 1054 x 1356 Packed Dimension (WxDxH) mm 1826 x 1054 x 1356 Packed Dimension (WxDxH) mm 1826 x 1054 x 1356	Interior Finish		Stainless steel
Type of Cooling Type of Defrost Automatic, hot gas Refrigerant Rego Refrigerant Charge Refrigerant Rego Sommand Consumption Remery Class Dimax Ambient Sommand Consumption Remery Consumption Refrigerant Charge Refrigerant C	Interior Light		LED
Type of Defrost Automatic, hot gas Refrigerant R290 Refrigerant Charge g 2 x 148 Thermometer Yes Power and Consumption Energy Class D Max Ambient 35°C at 75% RH Energy Consumption kWh/24h 29.75 Annual Energy Consumption kWh/year 10859 Power 16 Amp Single Phase Commando Socket Input Power W 2560 Voltage / Frequency V/Hz 220-240/50 Noise Level dB(A) 58 Dimensions Internal Dimension (WxDxH) mm External Dimension (WxDxH) mm 1826 x 1054 x 1356 Packed Dimension (WxDxH) mm 1826 x 1054 x 1356	Cooling and Functions		
Refrigerant Charge g 2 x 148 Thermometer Yes Power and Consumption Energy Class D Max Ambient 35°C at 75% RH Energy Consumption kWh/24h 29.75 Annual Energy Consumption kWh/year 10859 Power 16 Amp Single Phase Commando Socket Input Power W 2560 Voltage / Frequency V/Hz 220-240/50 Noise Level dB(A) 58 Dimensions Internal Dimension (WxDxH) mm External Dimension (WxDxH) mm External Dimension (WxDxH) mm 1826 x 1054 x 1356 Packed Dimension (WxDxH) mm 2000 x 1150 x 1620	Type of Cooling		Ventilated
Refrigerant Charge g 2 x 148 Thermometer Yes Power and Consumption Energy Class D Max Ambient 35°C at 75% RH Energy Consumption kWh/24h 29.75 Annual Energy Consumption kWh/year 10859 Power 16 Amp Single Phase Commando Socket Input Power W 2560 Voltage / Frequency V/Hz 220-240/50 Noise Level dB(A) 58 Dimensions Internal Dimension (WxDxH) mm External Dimension (WxDxH) mm External Dimension (WxDxH) mm 1826 x 1054 x 1356 Packed Dimension (WxDxH) mm 2000 x 1150 x 1620	Type of Defrost		Automatic, hot gas
Thermometer Yes Power and Consumption Energy Class D Max Ambient 35°C at 75% RH Energy Consumption kWh/24h 29.75 Annual Energy Consumption kWh/year 10859 Power 16 Amp Single Phase Commando Socket Input Power W 2560 Voltage / Frequency V/Hz 220-240/50 Noise Level dB(A) 58 Dimensions Internal Dimension (WxDxH) mm External Dimension (WxDxH) mm 1826 x 1054 x 1356 Packed Dimension (WxDxH) mm 2000 x 1150 x 1620	Refrigerant		R290
Power and Consumption Energy Class D Max Ambient 35°C at 75% RH Energy Consumption kWh/24h 29.75 Annual Energy Consumption kWh/year 10859 Power 16 Amp Single Phase Commando Socket Input Power W 2560 Voltage / Frequency V/Hz 220-240/50 Noise Level dB(A) 58 Dimensions Internal Dimension (WxDxH) mm External Dimension (WxDxH) mm 1826 x 1054 x 1356 Packed Dimension (WxDxH) mm 2000 x 1150 x 1620	Refrigerant Charge	g	2 x 148
Energy Class Max Ambient S35°C at 75% RH Energy Consumption kWh/24h 29.75 Annual Energy Consumption kWh/year 10859 Power 16 Amp Single Phase Commando Socket Input Power W 2560 Voltage / Frequency V/Hz 220-240/50 Noise Level Dimensions Internal Dimension (WxDxH) mm 1826 x 1054 x 1356 Packed Dimension (WxDxH) mm 2000 x 1150 x 1620	Thermometer		Yes
Max Ambient 35°C at 75% RH Energy Consumption kWh/24h 29.75 Annual Energy Consumption kWh/year 10859 Power 16 Amp Single Phase Commando Socket Input Power W 2560 Voltage / Frequency V/Hz 220-240/50 Noise Level dB(A) 58 Dimensions Internal Dimension (WxDxH) mm External Dimension (WxDxH) mm 1826 x 1054 x 1356 Packed Dimension (WxDxH) mm 2000 x 1150 x 1620	Power and Consumption		
Energy Consumption kWh/24h 29.75 Annual Energy Consumption kWh/year 10859 Power 16 Amp Single Phase Commando Socket Input Power W 2560 Voltage / Frequency V/Hz 220-240/50 Noise Level dB(A) 58 Dimensions Internal Dimension (WxDxH) mm External Dimension (WxDxH) mm 1826 x 1054 x 1356 Packed Dimension (WxDxH) mm 2000 x 1150 x 1620	Energy Class		D
Annual Energy Consumption kWh/year 10859 Power 16 Amp Single Phase Commando Socket Input Power W 2560 Voltage / Frequency V/Hz 220-240/50 Noise Level dB(A) 58 Dimensions Internal Dimension (WxDxH) mm External Dimension (WxDxH) mm 1826 x 1054 x 1356 Packed Dimension (WxDxH) mm 2000 x 1150 x 1620	Max Ambient		35°C at 75% RH
Power 16 Amp Single Phase Commando Socket Input Power W 2560 Voltage / Frequency V/Hz 220-240/50 Noise Level dB(A) 58 Dimensions Internal Dimension (WxDxH) mm 1826 x 1054 x 1356 Packed Dimension (WxDxH) mm 2000 x 1150 x 1620	Energy Consumption	kWh/24h	29.75
Input Power W 2560 Voltage / Frequency V/Hz 220-240/50 Noise Level dB(A) 58 Dimensions Internal Dimension (WxDxH) mm External Dimension (WxDxH) mm 1826 x 1054 x 1356 Packed Dimension (WxDxH) mm 2000 x 1150 x 1620	Annual Energy Consumption	kWh/year	10859
Voltage / Frequency V/Hz 220-240/50 Noise Level dB(A) 58 Dimensions Internal Dimension (WxDxH) mm External Dimension (WxDxH) mm 1826 x 1054 x 1356 Packed Dimension (WxDxH) mm 2000 x 1150 x 1620	Power	16 Amp Single Phase Commando Socket	
Noise Level dB(A) 58 Dimensions Internal Dimension (WxDxH) mm External Dimension (WxDxH) mm 1826 x 1054 x 1356 Packed Dimension (WxDxH) mm 2000 x 1150 x 1620	Input Power	W	2560
Dimensions Internal Dimension (WxDxH) mm External Dimension (WxDxH) mm 1826 x 1054 x 1356 Packed Dimension (WxDxH) mm 2000 x 1150 x 1620	Voltage / Frequency	V/Hz	220-240/50
Internal Dimension (WxDxH) mm External Dimension (WxDxH) mm 1826 x 1054 x 1356 Packed Dimension (WxDxH) mm 2000 x 1150 x 1620	Noise Level	dB(A)	58
External Dimension (WxDxH) mm 1826 x 1054 x 1356 Packed Dimension (WxDxH) mm 2000 x 1150 x 1620	Dimensions		
Packed Dimension (WxDxH) mm 2000 x 1150 x 1620	Internal Dimension (WxDxH)	mm	
	External Dimension (WxDxH)	mm	1826 x 1054 x 1356
40ft Container Load pcs 12	Packed Dimension (WxDxH)	mm	2000 x 1150 x 1620
	40ft Container Load	pcs	12







Heated front glass