



Ventilated Scoop Ice Cream Display


## **Product Features**

- Fully automatic
- LED interior light with switch
- Double air flow ensures even cooling of 2 rows of pans
- Angled deck (11°) for a better display
- Acrylic rear sliding doors to display area
- Heated glass to help prevent condensation
- Accepts Napoli pans (not supplied)
- Alternative colour options available (POA)
- Hinged glass for easy cleaning
- Optional scoop wash (needs water & waste connection)

A premium gelato and ice cream display, the Super Capri is designed to give maximum visual impact. The cabinet has clean contemporary lines, with large glass panels coupled with crisp LED interior lighting to present your gelato in the best way possible. The display is angled towards the customer (at 11°) to give a better view of the produce. The unit also has a unique double airflow cooling system that allows separate cool air flow over each row of pans, allowing for more efficient cooling while reducing temperature differential over the product keeping it looking and tasting at its very best. The display has heated glass to the front, top and sides to reduce any chance of condensation build while the front glass hinges to allow cleaning. Standard colour options are RAL9003 (white) RAL9005 (black) RAL9022 Grey)

Measures and Content		
Serving Capacity		12 Napoli Pans (5 L)
Storage capacity (under)		No Under Storage
Total Display Area	m²	0.71
Temperature Range	°C	-20 to -14
Climate Class		7
Gross / Net Weight	kg	308 / 240
Gross / Net Volume	1	
Design and Material		
Feet / Legs		Adjustable Feet
Castors		Castors
Exterior Finish		Grey RAL7022
Interior Finish		Stainless steel
Interior Light		LED
Cooling and Functions		
Type of Cooling		Ventilated
Type of Defrost		Automatic, hot gas
Refrigerant		R290
Thermometer		Yes
Power and Consumption		
Energy Class		D
Max Ambient		35°C at 75% RH
Energy Consumption	kWh/24h	21.85
Annual Energy Consumption	kWh/year	7976
Power	16 Amp Single Phase Commando Socket	
Input Power	W	1050
Voltage / Frequency	V/Hz	220-240/50
Dimensions		
Internal Dimension (WxDxH)	mm	
External Dimension (WxDxH)	mm	1187 x 1110 x 1175
Packed Dimension (WxDxH)	mm	1400 x 1400 x 1600
40ft Container Load	pcs	8







Double airflow cooling