



in association with



Inspired by Scandinavia

WMC743 Washing Machine

7

Kg Load



Steel Seal™



Active Drum™

530

G-Factor

Shortest cycle time

00:40

Super Quick Wash 60°C

Quick Overview

- Maximum spin speed: 1400 rpm
- Finish: Touch Proof™ Stainless steel
- 28 programmes including three custom programmes
- Relay card for auto dosing with three signals
- Anti-leakage system and child lock
- ECO cold and hot water connection - saves up to 70% of electrical consumption and 20% of the programme time
- Connection: 230V / 1ph / 16A / 50Hz / Max effect: 3.2kW
- Can be reconfigured to: 230V / 1ph / 10A / 50Hz / Max effect: 2.2kW or 400V / 3ph / 10A / 50Hz / Max effect: 3.2kW
- Available with pump or valve drain system

Marine specification model available



Construction

Operating position: Front-operated

Capacity: 7kg

Door opening: 31cm

Door opening angle: 180°

Door opening: Left hinge

Material: Stainless steel

Lifters in drum: Removable for easy cleaning

Base plate: Waterproof

Electrics

Connection power: 3,200W

Fuse: 16A

Electrical connection: 230V

Frequency: 50Hz

Length of power cable: 2.1m

Phases: 1

Connection of water/drain

Cold and hot water connection: Size 3/4" (adapter 1/2" included)

Inlet hose: PEX inlet hose, able to withstand 10 bar at 95°C (tested to over 50 years)

Drainage capacity: 20l/min

Drain system: Drain valve or pump available

Dimensions

Dimensions (H x W x D): 850 x 595 x 585mm

Packaging dimensions: 920 x 640 x 660mm

Net weight: 79kg

Gross weight: 85kg

Adjustable feet: 10mm

Depth with door open: 965mm

Inlet hose, length: 1,500mm

Inlet hose: 1,600mm

WMC743 Washing Machine



Drain pump version shown



Properties
Balance control: Protects the washer against harmful vibrations
Foam control: Sensors detect foam levels and automatically begin to remove excess foam
Emergency opening function: Standard
Maximum inlet time: Machine stops if correct water level is not achieved within a specified time
Water overfill protection: Standard
Remaining operating time: Shown on digital display
Protection against overheating: Thermal and electronic

Performance
Residual humidity: 53%
Heater power: 3,000W
Temperature range: Cold - 90°C

Programmes		
Normal 60°C	Wool/Hand wash 30°C	Allergy cotton 60°C
Normal 40°C	Rinse	Allergy cotton 40°C
Heavy 90°C	Mop 60°C	Allergy synthetics 60°C
Heavy 60°C	Mop 90°C	Allergy synthetics 40°C
White 90°C	Microfibre 60°C	Cleaning
White/Colour 60°C	Microfibre 40°C	Customisable Programme A
White/Colour 40°C	Disinfection 1 + 20 min 40°C	Customisable Programme B
Super Quick wash 60°C	Disinfection 2 + 60 min 60°C	Customisable Programme C
Super Quick wash 40°C	Disinfection 3 + 10 min 90°C	
Synthetics 40°C	Allergy cotton 90°C	

Operations
Display type: LCD display
Language: DA, DE, EN, ES, FI, FR, IT, NL, NO, RU, SV
Dispenser: Manual pull-out
Detergent dispenser: Three compartment dispenser

Options
Communication interface (MODBUS)
Card payment system
Coin payment system

DC Products

Unit 25 Lodge Hill Industrial Park, Westbury Sub Mendip, Somerset, BA5 1EY

t: 01749 870055 e: sales@dcproducts.co.uk w: www.laundry.dcproducts.co.uk